Dane aktualne na dzień: 24-11-2026 13:35

Link do produktu: https://www.nobshop.pl/aio-f722-taker-45a-32bit-p-5212.html

AIO F722 Taker 45A 32Bit



Cena brutto	**389,00 zł**
Cena netto	**316,26 zł**
Dostępność	**Aktualnie niedostępny**
Czas wysyłki	**1 - 3 dni**
Kod producenta	**GP107658**
Producent	**GepRC**

Opis produktu

AIO F722 Taker 45A 32Bit

The TAKER F722 45A 32Bit AIO features the STM32F722 MCU paired with the ICM42688-P (SPI) gyro, delivering powerful performance and fast processing.
It offers 5 full UART ports to support various external devices. A dedicated 6-pin port on the bottom allows direct plug-in for HD VTXs, reducing soldering and simplifying installation.
The 32-bit ESC firmware provides smooth control. Supports 2–6S batteries input, 45A continuous current, and 55A burst (10s). It also supports OSD tuning, buzzer, LED, and more, all in a lightweight 9.2g package.

Feature

1. Smooth throttle response with 32-bit ESC firmware.
2. Built-in barometer, compatible with INAV firmware.
3. Equipped with 42688-P gyro for stable and reliable performance.
4. Supports 2–6S battery input, 45A continuous current, 55A burst (10s).
5. Direct plug-in support for HD VTXs, no soldering, and easy installation.
6. Powered by STM32F722 MCU for faster processing.
7. Integrated 16MB Blackbox for flight data logging.
8. Supports OSD tuning, buzzer, LED, and more.
9. Features 5 full UART ports for connecting various external devices.

Specifications

- Model: TAKER F722 45A 32Bit AIO
- MCU: STM32F722
- IMU: ICM 42688-P (SPI
- Firmware Target: GEPRC_F722_AIO
- Blackbox: 16Mb on-board flash memory
- OSD: Betaflight OSD w/ AT7456E chip
- Uart: R1 T1 / R2 T2 / R3 T3 / R4 T4 / R5 T5
- Buzzer: YES
- LED: YES
- USB: Type-C USB
- BEC Output: 5V@1A
- ESC: 32Bit 45A
- Continuous Current: 45A
- Burst Current: 55A(10A)
- Input Voltage: 2~6S (LIPO)
- ESC Protocol: Dshot600, Oneshot, Multishot
- Dimension: 35mm * 33.5mm
- Mounting Hole Size: 25.5 mm * 25.5mm φM3 damping to M2 screw
- Weight: 9.2g

Includes

1× TAKER F722 45A AIO FC

1× XT30-18AWG wire-7cm

1× 35V 220µF capacitor

1× SH1.0-6Pin to GH1.25-8Pin adapter cable

1× SH1.0-6Pin cable

8× M2×6.5mm FC dampening balls (black)