

Link do produktu: <https://www.nobshop.pl/aio-geprc-taker-f722-35a-32bit-p-5262.html>

AIO GepRC Taker F722 35A 32Bit



Cena brutto	299,99 zł
Cena netto	243,89 zł
Dostępność	Dostępny
Czas wysyłki	1 - 3 dni
Kod producenta	GP108181
Producent	GepRC

Opis produktu

AIO GepRC Taker F722 35A 32Bit

The TAKER F722 35A 32Bit AIO features the STM32F722 MCU paired with the ICM42688-P (SPI) gyro, delivering powerful performance and fast processing.

It offers 5 full UART ports to support various external devices. A dedicated 6-pin port on the bottom allows direct plug-in for HD VTXs, reducing soldering and simplifying installation.

The 32-bit ESC firmware provides smooth control. Supports 2-6S batteries input, 35A continuous current, and 45A burst (10s). It also supports OSD tuning, buzzer, LED, and more, all in a lightweight 9.3g package.

Feature

1. Smooth throttle response with 32-bit ESC firmware.
2. Built-in barometer, compatible with INAV firmware.
3. Equipped with 42688-P gyro for stable and reliable performance.
4. Supports 2-6S battery input, 35A continuous current, 45A burst (10s).
5. Direct plug-in support for HD VTXs, no soldering, and easy installation.
6. Powered by STM32F722 MCU for faster processing.
7. Integrated 16MB Blackbox for flight data logging.
8. Supports OSD tuning, buzzer, LED, and more.
9. Features 5 full UART ports for connecting various external devices.

Specifications

- Model: TAKER F722 35A 32Bit AIO
- MCU: STM32F722
- IMU: ICM 42688-P (SPI)
- Firmware Target: GEPRC_F722_AIO
- Blackbox: 16Mb on-board flash memory
- OSD: Betaflight OSD w/ AT7456E chip
- Uart: R1-T1 / R2-T2 / R3-T3 / R4-T4 / R5-T5
- Buzzer: YES
- LED: YES
- USB: Type-C USB
- BEC Output: 5V@1A
- ESC: 32Bit 35A
- Continuous Current: 35A
- Burst Current: 45A(10A)
- Input Voltage: 2~6S (LIPO)
- ESC Protocol: Dshot600, Oneshot, Multishot
- Dimension: 35mm * 33.5mm
- Mounting Hole Size: 25.5 mm * 25.5mm ϕ M3 damping to M2 screw

-
- Weight: 9.3g

Includes

1× TAKER F722 35A AIO FC

1× XT30-18AWG wire-7cm

1× 35V 220μF capacitor

1× SH1.0-6Pin cable

8× M2×6.5mm FC dampening balls (black)

Manual

[TAKER F722 35A 32Bit AIO Manual](#)