Dane aktualne na dzień: 06-11-2026 21:04

Link do produktu: https://www.nobshop.pl/czujnik-wysokosci-radiomaster-ers-ba01-p-5218.html



Czujnik wysokości Radiomaster ERS-BA01

Cena brutto	**92,99 zł**
Cena netto	**75,60 zł**
Dostępność	**Dostępny**
Czas wysyłki	**1 - 3 dni**
Numer katalogowy	**RM0157.ERS-BA01**
Producent	**Radiomaster**

Opis produktu

Czujnik wysokości Radiomaster ERS-BA01

The ERS-BA01 Barometer Sensor provides accurate, real-time altitude data for compatible ExpressLRS receivers. By capturing barometric pressure and converting it into precise relative altitude information, the ERS-BA01 delivers reliable telemetry back to your EdgeTX radio. This sensor provides clear, responsive altitude monitoring.

As part of the ERS sensor family, the ERS-BA01 also supports pass-through expansion, allowing easy daisy-chaining with additional telemetry modules.

Launch Video

Features

- **Real-Time Altitude Telemetry:** Converts barometric pressure measurements into accurate relative altitude data for instant feedback on your radio.
- **Expansion-Ready Pass-Through:** Includes an in-and-out port for daisy-chaining additional ERS sensors without rewiring your setup.
- **Seamless ExpressLRS Compatibility:** Integrates easily with supported ExpressLRS PWM receivers via CRSF for fast and dependable data transmission.

Plug and Play Compatible Receivers:

- ER6 2.4GHz ExpressLRSPWM Receiver
- ER8 2.4GHz ExpressLRSPWM Receiver
- ER8G & ER8GV ExpressLRS PWM Receiver

Using Sensors with Non-Plug-and-Play PWM ExpressLRS Receivers:

Most PWM ExpressLRS receivers are fully compatible; those without a dedicated UART port require reconfiguration to support external sensors (e.g., for telemetry). To enable this, reassign two PWM output pins as a serial UART—one for TX and one for RX—via the receiver's Web UI (accessed by putting the receiver into WiFi mode) or via the ExpressLRS LUA script. This enables sensor connectivity while preserving the remaining PWM channels for servos or ESCs.

For receivers that only provide standard servo pins, an optional adapter cable is available that converts the sensor’s UART connector to two standard servo plugs (TX and RX).

Sensor Configuration & Telemetry Logging

To configure this sensor and view telemetry on your EdgeTX radio, install the RadioMaster Sensor Configurator LUA. The LUA

allows adjustment of sensor settings, enables proper telemetry display, and supports data logging for post-flight review.

After downloading, connect your radio to a Mac or PC in USB-SD mode.

Copy the LUA files to:
/SCRIPTS/TOOLS/

Specifications

- Item: ERS-BA01 Barometer Sensor
- Operating voltage: 5–8.4V
- Operating current: 9mA
- Altitude accuracy: ±0.5m
- Temperature range: –10 ℃ to +85 ℃
- Size: 23.5 × 13 × 7mm
- Weight: 3.5g

Size

Weight

Package Includes

- 1 * ERS-BA01 Precision Barometric Altitude Sensor
- 3 * Heat-Shrinkable Tube
- 1 * Manual QR Code Card