Dane aktualne na dzień: 05-11-2026 07:43

Link do produktu: https://www.nobshop.pl/dron-iflight-taurus-x8-hd-cinelifter-w-dji-air-unit-p-2791.html



Dron Iflight Taurus X8 HD Cinelifter w/ DJI Air Unit

Cena brutto	**8 399,99 zł**
Cena netto	**6 829,26 zł**
Dostępność	**Na zamówienie**
Czas wysyłki	**14 dni**
Producent	**iFlight**

Opis produktu

Product Description

Let's introduce our new **iFlight Taurus X8** BNF, our heavy duty gear to lift those big cams!

Engineered with professionals for professionals, a BNF that's aimed for carrying big payloads offering a soft-damped universal platform for DSLR or cinema cameras (Red Komodo, Zcam, BMPCC, etc) featuring DJI's FPV HD transmission system. Redundant ESC and motor setup for maximum performance but also a safety factor. Even in case of an overload or failure, one remaining ESC and 4 motors will be able to carry your expensive camera back to you. In case you get troubles with signal interference, radio signal loss, or complete FPV transmission fail the GPS rescue feature will automatically take over control, climb to max flight altitude, and descent towards your liftoff location until the signal transmission is regained (no automated landing). The integrated TPU landing gear provides sufficient height for most terrain and offers some protection on harder landings.

2kg maximum payload for a variety of top-mounted cameras and the ability to fine-adjust the stable mount for a perfectly balanced CG (Center of Gravity). The underslung battery acts as a power source as well as a counterweight to strategically slide the weight more front or back to counter camera lenses of different weight or length. The adjustable CNC aluminum mount offers angles from 5 to 35 degrees and can be safely secured for reproducible outcomes. No jello, no jitter, no problem; Our silicon-ball dampened carbon camera base is decoupled from the rest of the frame to reduce the amount of vibration generated by motors and propellers. For the perfect cinematic shot we recommend and additional software stabilization in the post or a hardware module (for example SteadXP).

The estimated flight time with 6S 4500mAh and attached cinema camera is about 4-6min, depending on speed and wind conditions! (set includes one battery)

Features:

- XING 2806.5 efficient and powerful wide stator motors
- Redundant ESC and motor configuration
- Stable silicon-ball decoupled camera CNC mount
- GPS flight data and rescue functionality
- 2kg max payload for various cinema and DSLR cameras
- Optimized CG through the adjustable camera and battery mount