

Link do produktu: <https://www.nobshop.pl/f4-1s-aio-bezszczotkowy-kontroler-lotu-betafpv-frsky-v21-meteor65-p-1794.html>



F4 1S AIO bezszczotkowy kontroler lotu BetaFPV FrSky V2.1 Meteor65

Cena brutto	169,00 zł
Cena netto	137,40 zł
Dostępność	Aktualnie niedostępny
Czas wysyłki	1 - 3 dni

Opis produktu

This is the lightest F4 1S brushless FC in the current market. With BT2.0 connector, slim and sleek design, 2.69g in weight and better performance on function for maximum weight savings, power, and responsiveness.

Equips with BT2.0 connector, all 1S brushless drones will gain stronger powerful and perfect performance. Specially made for 1S brushless whoop with F411 chip. A great choice for building [Beta65 Pro](#) and [Beta75 Pro](#).

If you own an initial PH2.0 connector FC but want to try the new BT2.0 connector, you could get the [BT2.0 connectors](#) FREE and re-solder it.

[Know more about the BT2.0 connector.](#)

Ultra-compact with 2.69g weight(No include power cable), this FC is ready and waiting to take residence within your 1S micro FPV aircraft of choice, which could save much weight for a faster fly experience.

Want to try Silverware firmware on your 1S brushless drone, please check the [Lite 1S flight controller](#) board.

SPECIFICATIONS OF FC

- CPU: STM32F411CEU6 (100MHZ)
- Six-Axis: MPU-6000 triaxial accelerometer / triaxial gyroscope (SPI connection)
- Size: 29mm x 29mm, fully compatible with the whoop frame in the current market, [Beta65 Pro frame](#), [Beta75 Pro frame](#), BWhoop B06 frame, and mounting pattern
- Firmware version: Frsky
- Compatible with [Z02](#), [A01](#), [M01](#) VTX
- OSD: Built-in BetaFlight OSD (STM32 controls OSD chip over SPI in DMA mode)
- Power Cable: 55mm, with BT2.0 connector
- Weight: 2.69g

SPECIFICATIONS OF ESC

- Power supply: 1S
- Current: 5A continuous and peak 6A (3 seconds)
- Support BLHeliSuite programmable
- Factory firmware: O_L_5_REV16_6.HEX
- Signal Support: D-shot150, D-shot300, D-shot600, Oneshot125, Multishot, PWM