

Link do produktu: <https://www.nobshop.pl/kamera-fpv-foxeer-digisight-2-nano-720p-8mp-p-2972.html>

Kamera FPV Foxeer Digisight 2 Nano 720p 8mp



Cena brutto	225,99 zł
Cena netto	183,73 zł
Dostępność	Aktualnie niedostępny
Czas wysyłki	1 - 3 dni
Producent	Foxeer

Opis produktu

Kamera FPV Foxeer Digisight 2 Nano 720p 8mp

Foxeer Digisight 2 Nano to kamera FPV, która poprzez nowatorskie zastosowanie 2 złączy przeznaczona jest zarówno do analogowego systemu wizji jak i cyfrowego przystosowanego pod jednostkę DJI Air Unit czy też Caddx Vista itp. Kamera posiada opóźnienie przesyłu obrazu na poziomie 4ms, przez co nadaje się idealnie do dronów wyścigowych jak i freestyle. Wbudowany WDR idealnie dobiera ustawienia ekspozycji powodując, że w goglach pilot dostrzeże każdy szczegół. Dzięki wbudowanemu OSD nie potrzebny jest zewnętrzny moduł, wszystkie ważne informacje są na wyciągnięcie ręki. W trybie analogowym kamera posiada rozdzielczość 1000TVL przy zasilaniu 4,5-20V, natomiast w trybie cyfrowym jakość obrazu jest w rozdzielczości HD 720p przy napięciu 3,3V.

Specyfikacja:

Sensor Type	Sony 1/3" CMOS Sensor
Scale	4:3(default)/16:9 Switchable
Tv System	PAL(default)/NTSC Switchable
Resolution	Digital 720P/Analog 1000TVL
Shutter Speed	PAL 1/25~1/10000 sec; NTSC 1/30~1/10000 sec
Video Output	720P Digital HD/CVBS Analog Signal
FOV	Digital: FOV-H:120° FOV-D: 145°
	Analog: FOV-H:125° FOV-D: 155°
Shutter Speed	Auto
Minimum Illumination	0.01Lux
White Balance	Auto
DNR	3DNR 2DNR
WDR	120dB
Mode	DAY/CLOUDY/Night/LED
Fast Mode Switch	Long Press Right Button to switch among DAY/CLOUDY/Night/LED
Flight OSD	Cam Title / Voltage (Only in analog) / Time
Input Power	Digital: 3.3V from VTx
	Analog: 4.5~20V
Language	ENGLISH/ DEUTSCH/ FRANCAIS/ PYCCKNN/ PORTUGUES/ ESPANOL/ □□
Working Temperature	-10°~50°C RH90% MAX
Working Humidity	20~80%
Storage Temperature	-20°~70°C
Menu	Analog via camera programming board, Digital via VTx and Cam board
Consumption	Analog:50mA±15% @ DC12V 115mA±15% @ DC5V
	Digital:350mA@3.3V(Powered by VTX)
Cable Length	150mm

Dimension	14*14mm; 19*19mm(Add Bracket)
Weight	4.3g(Exclude cable)