

Dane aktualne na dzień: 19-04-2026 23:12

Link do produktu: <https://www.nobshop.pl/modul-elrs-emax-aeris-link-micro-expresslrs-868mhz-915mhz-900mhz-p-4591.html>



Moduł ELRS EMAX Aeris Link Micro ExpressLRS 868MHz / 915MHz / 900MHz

Cena brutto	259,00 zł
-------------	------------------

Cena netto	210,57 zł
------------	------------------

Dostępność	Dostępny
------------	-----------------

Czas wysyłki	1 - 3 dni
--------------	------------------

Producent	EMAX
-----------	-------------

Opis produktu

Moduł EMAX Aeris Link Micro ExpressLRS 868MHz / 915MHz

Aeris Link Micro to moduł ELRS 868/915 o maksymalnej mocy 1W, w obudowie w standardzie JR/micro, z możliwością zewnętrznego zasilania przez port XT30 i sterowania z poziomu radia przez skrypt Lua bądź przez joystick i wyświetlacz na module.

AERIS LINK



EMAX ELRS

Prepare to experience FPV flying like never before with the revolutionary EMAX AERIS LINK. This sophisticated open-source ELRS transmitter is meticulously designed to deliver unmatched performance and elevate your FPV adventures to new heights.



USER FRIENDLY

Equipped with a 1.29-inch OLED screen, the AERIS LINK presents essential flight control with clarity and ease. The user-friendly interface empowers you to fine-tune settings and control your crafts in real-time, granting you complete control over your FPV experience.



POWER REFINED

Harness the true potential of the EMAX AERIS LINK's transmission capabilities. From the ability to pick an output power of 10mW to the option to adjust up to a formidable 1000mW, you'll achieve unparalleled range and signal stability. Conquer challenging terrains and explore uncharted skies with confidence.



OPEN-SOURCE

The AERIS LINK is engineered for versatility and ease of use. It supports Crossfire Serial Data Protocol (CRSF) and OpenTX remote control signals, ensuring seamless compatibility with your preferred setup. The Type-C interface and J1 interface facilitate hassle-free connections for a seamless FPV experience.



POWER UP

Rely on the AERIS LINK's XT30 interface for external power. It accommodates a voltage input range of 5-21V, with a recommended 2S (8.4V) power source for optimal performance and reliability during your flights.



2.4G VS 915M

With options from 2.4G to a longer range 915M, elevate your FPV game with the EMAX AERIS LINK, where innovation meets reliability. Experience the freedom to customize, the power to transmit with confidence, and the promise of unparalleled performance.

