

Link do produktu: <https://www.nobshop.pl/nadajnik-wideo-analogowy-12g-geprc-maten-2w-p-5144.html>



Nadajnik wideo analogowy 1.2G GepRC Maten 2W

Cena brutto	244,99 zł
Cena netto	199,18 zł
Dostępność	Dostępny
Czas wysyłki	1 - 3 dni
Kod producenta	GP106232
Producent	GepRC

Opis produktu

Nadajnik wideo analogowy 1.2G GepRC Maten 2W

Summary

The MATEN 1.2G 2W VTX high-power image transmission newly developed by the GEPRC team is now officially released. Its performance is very powerful, with 4 adjustable power levels and a maximum power of up to 2000mW. The transmission signal is very stable and the penetration ability is excellent.

MATEN 1.2G 2W VTX uses high-strength aluminum alloy CNC shell to assist heat dissipation. The unique appearance design stronger impact resistance and better heat dissipation performance.

It supports the IRC Tramp protocol and can use the OSD to quickly adjust parameters.

It has a wide voltage input of 7-36V and temperature control protection function to prevent overheating and burning. Support 30.5×30.5mm(M3) installation hole position.

Feature

1. Four levels of adjustable power, up to 2000mW, suitable for long distance flight
2. optional channels
3. Selected high strength aluminum alloy CNC shell, auxiliary heat dissipation
4. Wide voltage input, Supports 7V-36V Voltage input.
5. One function buttons, two indicator lights, easy to control.
6. VTX control protocol is IRC Tramp, supports OSD parameter adjustment.
7. Temperature control protection function that can prevent high temperature burning
8. Support 30.5×30.5mm(M3) installation hole position

Specifications

- Model GEPRC MATEN 1.2G 2W VTX
- Size 36.4×36.4×7.4mm
- Mounting hole 30.5×30.5mm(M3)
- Frequency band 1080MHz-1360MHz
- Channel customer 9
- Channel Frequency 1080/1120/1160/1200/1240/1280/1320/1360/1220(MHz)
- Output power 25mW/400mW/800mW/2000mW/Pit mode
- Frequency Stability ±100KHz (Typ.)
- Frequency precision ±200KHz (Typ.)
- S/N(Fo±3MHz) >70dBc
- Antenna Port 50 Ohms
- Input voltage DC7-36V 2-8S Battery
- Output voltage 5V@600mA

-
- Protocol□IRC Tramp
 - Antenna interface□MMCX
 - Cable interface□sh1.25 6pin
 - Video format□PAL/NTSC
 - Operating Temperature□-10°C~+60°C
 - Weight□14.5g□VTX only□

Notes

1. Install Antenna before use.
2. To prevent overheating,provide constant airflow and a well ventilated environment.Install a cooling fan if operating in confined conditions.
3. The 5V Output is for a Camera/Cooling Fan use only!Do not connect Power Input/Battery to 5V Out. Serious damage will occur to VTX.

Includes

- 1 x MATEN 1.2G 2W VTX
- 1 x MMCX to SMA□internal needle□connector
- 1 x 1.2G antenna(SMA inner hole)
- 1 x sh1.25 6P Connecting cable
- 5 x M3*7 screws
- 5 x M3*8 screws
- 5 x M3 x 10 hexagon
- 5 x M3*5 isolation column
- 5 x M3 nylon nut
- 1 x product description