Dane aktualne na dzień: 19-11-2026 16:57

Link do produktu: https://www.nobshop.pl/rama-speedybee-mario-5-o4-pro-p-4363.html

Rama SpeedyBee Mario 5 O4 Pro



Cena brutto	**204,99 zł**
Cena netto	**166,66 zł**
Dostępność	**Aktualnie niedostępny**
Czas wysyłki	**1 - 3 dni**
Producent	**SpeedyBee**

Opis produktu

Rama SpeedyBee Mario 5

Specyfikacja:
Rozmiar Mario 5 DC: 227mm,
Waga Mario 5 DC:
  129±5g (bez druków 3D),
  170±5g (z drukami 3D i plastikowymi osłonami),
Rozmiar Mario 5 XH: 226mm,
Waga Mario 5 XH:
  126±5g (bez druków 3D),
  167±5g (z drukami 3D i plastikowymi osłonami),
Grubość górnej płyty: 2.5mm (T300 3K),
Grubość środkowej płyty: 2.0mm (T300 3K),
Grubość dolnej płyty: 2.5mm (T300 3K),
Grubość ramion: 6mm (T300 3K),
Rozmiar śmigieł: max 5.1 cala,
Rozstaw śrub montażowych silnika: 16-19mm,
Otwory montażowe FC / ESC / AIO: 30.5x30.5(M3),
Otwory montażowe nadajnika wideo: 20x20(M2) / 25.5x25.5(M2),
Materiał kabinki na kamerę: stop aluminium lotniczego,
Wysokość wewnątrz ramy: 23-31mm,
Przestrzeń na montaż odbiornika: 25*13*6mm,
Maksymalny rozmiar kondensatora: Φ10mm*20mm,
Rozmiar modułu GPS: 18*18*7.


MARIO 5
FREE FLIGHT
SpeedyBee
By Lema fpv
MARIO 5 DC
(DJI O3 Propeller-free View)
MARIO 5 XH
(Ideal with Gopro)
Wheelbase: 227mm
Weight: 129 ±5g (3D Printed Parts Excluded)
170 ±5g (3D Printed Parts and Injection -Molded Parts Included)
Wheelbase: 226mm
Weight: 126 ±5g (3D Printed Parts Excluded)
167±5g (3D Printed Parts and Injection -Molded Parts Included)
MARIO 5 DC and MARIO 5XH: Interchangeable parts for easy swapping.


Creating 3D Files ?
Adding GPS ?
Cooler Colors ?
.....
Flashier LEDs ?
Dual Antennas ?
DIY
Free Combination
MARIO 5 DC Lite Version
DIY your own 3D printed models and colors as desired.
MARIO 5 DC Advanced Version
(Lite + Upgrade Kit A)
Simplify learning, save time, and elevate aesthetics.
MARIO 5 DC PRO Version
(Lite + Upgrade Kit A+ Upgrade Kit B)
Enhanced device protection and improved aesthetics.

Top Plate Thickness:	2.5mm (T300 3K)
Middle Plate Thickness:	2.0mm (T300 3K)
Bottom Plate Thickness:	2.5mm (T300 3K)
Arm Thickness:	6mm (T300 3K)
Camera Mounting Screw:	7mm
3D Printed Parts:	Yellow TPU
Battery Anti-Slip Pad:	Silicone 3mm
Motor Spring Hole Position:	⌀ 8mm
Compatible Propeller Size:	Max 5.1 Inch
Motor Mounting Hole Distance:	16-19mm
FC Mounting Hole:	30.5X30.5(M3)
VTX Mounting Hole:	20X20(M2) / 25.5X25.5(M2)
Head Material:	Aviation Aluminum Alloy
Aluminum Column Material:	7075 D5*23mm/D46*22mm
Internal Mounting Height:	23-31mm
Receiver Installation Space:	25*13*6mm
Suitable Capacitor Size:	⌀ 10mm*20mm
GPS Installation Size:	18*18*7


High-Strength Alloy Head

The MARIO series features a high-strength aviation aluminum alloy head, designed to protect the lens, meet DJI O3 VTX ultra-wide-angle requirements, and offer an impressive visual experience.

Product features



- Enhances HD VTX to minimize high -frequency 'jello effect' for a steadier image.
- Recessed Gopro Mount,Provides a lower center of gravity compared to standard mounts.


Unique Support Structure
Unique carbon plate arm support structure: enhances body stability, minimizes twisting, and accommodates capacitor installation.
Product features
Capacitor installation size: (⦸ 10mm*20mm)
Supports dual-directional installation.
Power Dual Input Method
Selectable dual main power input for easy adjustment of drone's center of gravity, with integrated socket and antenna for a neater installation.
Product features
Capacitor installation space allows for neater DIY wiring.


Receiver Installation Space
The rear bottom area is dedicated for receiver installation. Simply remove the protective cover at the bottom for easy frequency binding.
Product features
Installation Space Dimensions: 25mm*13mm*6mm)
Translucent Protective Cover: Simplifies receiver binding and provides clear visibility of receiver lights.
Diverse OpenSource 3D Models
Choose from a variety of 3D models to suit your functional and color preferences. We encourage more designers to contribute to MARIO model's 3D parts.
Product features
Ongoing design and open-source for diverse usage.

Frame Protection Armor

MARIO5's protective armor consists of two sections: the front protects the FC, while the rear enhances DJI O3 heat dissipation, significantly improving O3 VTX cooling capacity.

Product features



Enhance the aesthetics with RGB ambient lighting while ensuring FC protection for a stylish appearance.


Lightweight Protective Footpads

Lightweight injection-molded motor protection footpads minimize inertia while ensuring motor and frame protection.

Product features



Lightweight protective footpads, compatible with motors with hole spacing of 16–19mm.


MARIO 5 DC Lite
Package:
Top Plate （1）
Middle Plate（1）
Bottom Plate （1）
Supporting Board（2）
Front Arm （2）
Back Arm（2）
D46 M3*22mm
Aluminum Column（3）
D5 M3*23mm
Aluminum Column（6）
Head L （1）
Head R （1）
Motor Protective Pad （4）
Receiver Protective
Cover（1）
Battery Anti-Slip Pad（1）
Camera Silicone Mount（2）
M3*16 Screw（4）
M3*25 Screw（4）
M1.6*8 Screw（4）
M2*4 Screw（4）
M2*7 Screw（6）
M3*6 Screw（14）
M3*12 Screw（8）



MARIO 5 XH Lite

Package:



Top Plate（1）



Middle Plate（1）



Bottom Plate（1）



Arm（4）



Supporting Board（2）



Battery Anti-Slip Pad（1）



D46 M3*22mm
Aluminum Column（3）



D5 M3*23mm
Aluminum Column（6）



Head L （1）



Head R （1）



Motor Protective Pad（4）



Receiver Protective
Cover（1）



M1.6*8 Screw（4）



M2*4 Screw（4）



M2*7 Screw（6）



M3*6 Screw（14）



M3*12 Screw（8）



M3*16 Screw（4）



M3*25 Screw（4）



Camera Silicone Mount（2）

Produkt posiada dodatkowe opcje:

Wersja: DC Advanced , DC Lite , DC Pro , XH Advanced , XH Pro