

Dane aktualne na dzień: 11-05-2026 21:08

Link do produktu: <https://www.nobshop.pl/silnik-iflight-xing-2-3110-p-4102.html>



Silnik iFlight Xing 2 3110

Cena brutto	200,00 zł
Cena netto	162,60 zł
Dostępność	Dostępny
Czas wysyłki	1 - 3 dni
Producent	iFlight

Opis produktu

Silnik iFlight Xing 2 3110

Our XING series NextGen motors have become popular after the initial release in 2018 and became the new standard on the market. Was it the curved shape or the internal damping ring to protect the bearing, or was it the higher quality NSK bearings coupled with a higher grade titanium alloy shaft? We've been copied and compared all these years, but now it's time to set a new standard again! We're finally ready to announce our predecessor the XING2!

The smooth, reliable and powerful XING motors were upgraded and we achieved an even higher standard in our manufactory as well as better performance than ever before. New center slotted N52H curved arc magnets were introduced to drastically reduce response time of the motor! Maybe the biggest bottleneck of our FPV flight controller is the motor due to it's translation delay of it braking and accelerating. XING2 motors offer faster response to translate your PID loop quicker and get that locked-in feeling you were always looking for!

Due to the high quality materials used and the durable joint of bell and shaft, we were able to reduce the magnet air gap and stator lamination to a minimum. The smaller the air gap is, the lower that reluctance and the higher the magnetic flux (which is the magnetic analog of current) causing more efficiency and higher power!

Features

5mm titanium alloy shaft, our strongest prop shaft ever!

Crash resistant 7075 aluminum bell

Smooth and long-lasting NSK 11x5x5 bearings

Center slotted N52H curved arc magnets

XING O-ring bearing gap protection

Motor wires protector

Dynamically balanced

Designed for 7/8/9 inch Cinelifter.

Specification

KV: 900/1250/1600KV

Weight(included wire): 77g

Dimension: ϕ 38.72*24.6mm

Interphase Resistance: 43m Ω

Input Volts: 25.2V

Peak Current: 84.68A

Max Watt: 1976.4W

Mounting Holes: 19*19 ϕ 3mm

Rotor Specifications: Unibell

Shaft Diameter: 4mm

Shaft Protruding Length: 15mm

Lead: 260mm/18AWG

Magnet: N52H Curved

Configuration: 12N14P

Bearing Type: NSK

Bearing Specification: ϕ 11* ϕ 5*5

Winding: Single Strand copper winding

Packing List

1 x XING2 3110 Brushless Motor

4 x M3x10 screws

1 x M5 Flange Nut

Produkt posiada dodatkowe opcje:

KV: 1600KV , 900KV