Dane aktualne na dzień: 14-11-2026 00:05

Link do produktu: https://www.nobshop.pl/smigla-t-motor-cine-10550-c105x53-1cw-1ccw-p-4381.html



Śmigła T-Motor Cine 10550 C10.5x5.3 1CW 1CCW

Cena brutto	**69,99 zł**
Cena netto	**56,90 zł**
Dostępność	**Aktualnie niedostępny**
Czas wysyłki	**1 - 3 dni**
Producent	**T-Motor**

Opis produktu

Śmigła T-Motor 10550 C10.5x5.3 1CW 1CCW


LARGE THRUST
load weight 1-4kg, take-off weight 4-9kg no
pressure on loaded shooting equipment



SMALL
VIBRATION
Reasonable structural design
less power loss, and longer
flight time
TO THE FREEDOM


HIGH EFFICIENCY
The blades are not easily deformed
parameter adjustment is simple, perfect for
fpv cinematic



Specyfikacja:

Product Drawing



Specifications

Model	C8.5X5	Hub Diameter	16.4mm
Includes	1x CCW Prop 1x CW Prop	Center Thickness	4mm
Blades	5	Hub Inner Diameter	5mm
Material	Glass fiber nylon	Maximum blade width	21.7mm
Pitch	5in	Weight	14.8g
Prop Disc Diameter	216mm	Recommended Power Combo	CM4004 1100KV/PP5X5C 4S6.4MM

Model	C10.5X5	Hub Diameter	12.2mm
Includes	1x CCW Prop 1x CW Prop	Center Thickness	4mm
Blades	5	Hub Inner Diameter	5mm
Material	Glass fiber nylon	Maximum blade width	25.5mm
Pitch	5in	Weight	21.5g
Prop Disc Diameter	240mm	Recommended Power Combo	V3115 1000KV/PP5X5C 4S6 4M3

Model	C9.5X5	Hub Diameter	13.6mm
Includes	1x CCW Prop 1x CW Prop	Center Thickness	4mm
Blades	5	Hub Inner Diameter	5mm
Material	Glass fiber nylon	Maximum blade width	24.3mm
Pitch	5in	Weight	19.7g
Prop Disc Diameter	267mm	Recommended Power Combo	V3125 500KV/PP5X5C 4S6 4Z5

Test Report

Motor	Propeller	Throttle	Voltage (V)	Current (A)	Power (W)	RPM	Thrust (g)	Torque (N*m)	Efficiency (g/W)	Temperature (°C)
		10%	24.07	0.73	17.60	2540	34.14	0.09	1.26	
		20%	24.08	2.66	64.42	3492	134.50	0.30	2.30	
		30%	24.00	5.53	132.82	3340	302.40	0.45	2.61	
		40%	23.92	9.30	222.50	3890	382.40	0.72	2.45	
5205/2 1150KV	CR10X5X3	50%	23.89	14.24	340.40	4353	1425.20	0.97	3.08	✓
		60%	23.77	23.18	547.60	5194?	1914.800	0.29	3.50	
		70%	23.82	33.75	794.00	5728	2464.210	0.38	3.10	
		80%	23.39	45.54	1065.10	6080	2932.340	0.45	2.75	
		90%	23.43	59.21	1312.34	6696	3324.420	0.53	2.47	
		100%	22.97	72.58	1668.70	7230	3892.570	0.60	2.25	
		10%	24.07	0.72	17.30	2458	34.250	0.05	4.95	
		20%	24.04	2.63	63.15	3306	266.010	0.06	5.00	
		30%	24.00	5.32	127.80	3332	656.990	0.11	5.25	
		40%	23.92	9.48	226.80	3717	1009.100	0.16	4.49	
CM4004 1150KV	CR10X5X3	50%	23.84	14.14	336.50	4464	1434.660	0.22	4.73	✓
		60%	23.77	22.86	542.00	5302	1953.690	0.30	3.54	
		70%	23.57	33.82	774.30	5998	2446.540	0.38	3.16	
		80%	23.40	44.28	1036.20	6604	2932.980	0.45	2.82	
		90%	23.26	57.92	1346.70	7204	3466.660	0.53	2.52	
		100%	22.95	72.12	1655.40	7695	3857.760	0.60	2.30	
		10%	24.03	0.35	8.40	2427	42.080	0.04	7.41	
		20%	24.02	1.45	34.82	4705	232.160	0.04	7.23	
		30%	24.00	3.66	87.80	5661	552.360	0.09	6.29	
		40%	23.93	7.43	177.70	6870	955.720	0.14	5.18	
5108B 1150KV	CR10X5X3	50%	23.85	12.41	297.80	7982	1542.580	0.23	5.13	✓
		60%	23.73	20.91	496.90	11153	1989.090	0.28	4.56	
		70%	23.57	30.54	719.80	12862	2435.160	0.36	3.84	
		80%	23.42	40.36	945.20	13879	2920.980	0.40	3.64	
		90%	23.22	54.33	1261.80	14623	2843.730	0.46	2.53	
		100%	23.02	68.42	1574.80	15292	3389.810	0.49	2.58	
		10%	24.05	0.33	7.80	2521	42.700	0.04	5.37	
		20%	24.02	1.35	32.30	4632	246.120	0.04	7.61	
		30%	23.99	3.38	79.50	5686	551.280	0.08	6.59	
		40%	23.94	6.98	167.10	6870	955.980	0.14	5.51	
F405 1100KV	CR10X5X3	50%	23.87	11.66	277.00	7891	1545.160	0.20	4.62	✓
		60%	23.78	19.38	411.80	11207	1964.270	0.25	4.83	
		70%	23.62	28.13	617.50	12731	2430.420	0.33	3.65	
		80%	23.47	37.38	877.30	13879	2920.980	0.40	3.33	
		90%	23.23	50.85	1181.30	14623	2843.730	0.46	2.41	
		100%	23.03	63.89	1471.70	15296	3389.540	0.54	2.30	

Motor	Propeller	Throttle	Voltage (V)	Current (A)	Power (W)	RPM	Thrust (g)	Torque (N*m)	Efficiency (g/W)	Temperature (°C)
		10%	24.05	0.36	8.61	2162	36.210	0.05	7.25	
		20%	24.03	1.53	31.80	4053	250.030	0.05	7.87	
		30%	23.99	4.16	75.50	5663	551.640	0.09	7.08	
		40%	23.95	8.19	148.00	7198	887.610	0.15	5.99	
5205/2 970KV	CR10X5X3	50%	23.88	16.81	258.00	8846	1373.350	0.23	4.96	✓
		60%	23.78	27.54	411.00	9915	1789.880	0.29	4.27	
		70%	23.65	39.50	579.30	11121	2190.360	0.32	3.78	
		80%	23.50	51.88	804.20	12368	2750.980	0.45	3.35	
		90%	23.35	65.53	1060.00	13070	3138.890	0.52	2.93	
		100%	23.10	77.99	1323.40	13595	3543.020	0.59	2.65	
		10%	24.05	0.51	7.90	2323	44.050	0.07	8.78	
		20%	24.02	1.53	31.80	3998	256.030	0.05	8.48	
		30%	23.99	4.16	74.90	5606	551.500	0.09	7.24	
		40%	23.95	8.18	150.90	7132	941.250	0.15	6.05	
CM4004 970KV	CR10X5X3	50%	23.88	16.93	261.50	8588	1320.430	0.23	5.06	✓
		60%	23.78	27.38	411.00	9844	1739.740	0.30	4.23	
		70%	23.65	39.99	590.80	11089	2252.360	0.37	3.82	
		80%	23.50	54.86	815.30	12192	2727.980	0.45	3.33	
		90%	23.35	65.18	1055.20	13062	3140.780	0.52	2.98	
		100%	23.10	78.01	1241.50	13595	3543.250	0.59	2.78	
		10%	48.05	0.21	10.08	2134	34.940	0.02	3.49	
		20%	48.02	0.76	35.40	4451	272.889	0.05	7.53	
		30%	48.02	1.46	70.00	5412	470.430	0.08	6.82	
		40%	47.99	3.11	149.20	7101	893.576	0.14	5.74	
5215 4000KV	CR10X5X3	50%	47.93	5.51	264.40	8442	1320.320	0.22	4.92	✓
		60%	47.91	8.01	412.30	10409	1750.810	0.29	4.21	
		70%	47.83	12.15	581.30	11455	2237.550	0.39	3.83	
		80%	47.73	17.46	833.80	12860	2686.330	0.50	3.18	
		90%	47.60	23.77	1131.00	14111	3448.710	0.61	3.01	
		100%	47.54	31.42	1465.40	15255	4290.180	0.72	2.88	
		10%	32.08	0.33	9.68	2041	32.200	0.03	3.05	
		20%	32.07	1.21	36.90	4448	242.278	0.04	6.25	
		30%	32.04	3.04	94.61	5943	516.000	0.09	6.72	
		40%	32.01	5.81	190.80	7765	881.906	0.14	5.56	
5215 3400KV	CR10X5X3	50%	31.96	9.72	278.50	9132	1323.480	0.22	4.79	✓
		60%	31.88	13.84	441.40	10972	1767.450	0.30	4.15	
		70%	31.80	18.42	617.90	11554	2288.360	0.39	3.87	
		80%	31.82	23.77	874.40	12900	2813.000	0.50	3.45	
		90%	31.33	27.44	1138.50	14120	3437.140	0.60	3.08	
		100%	31.36	49.83	1522.60	15211	4270.560	0.71	2.78	
		10%	24.05	0.49	11.80	3264	29.430	0.02	2.50	
		20%	24.03	1.88	45.30	4251	246.300	0.05	5.42	
		30%	24.00	3.88	93.10	5790	541.440	0.13	5.88	
		40%	23.96	7.48	177.50	7631	942.900	0.16	5.27	
5215 3000KV	CR10X5X3	50%	23.94	12.53	299.30	8930	1402.560	0.23	4.69	✓
		60%	23.52	20.83	489.70	10468	1903.730	0.32	3.88	
		70%	23.80	28.85	680.80	11723	2470.640	0.41	3.64	
		80%	23.63	40.01	951.30	13006	3083.880	0.53	3.24	
		90%	23.43	54.17	1257.80	14156	3962.890	0.61	2.91	
		100%	23.08	70.01	1608.90	15190	4240.050	0.73	2.64	
		10%	24.06	0.63	15.70	3721	29.900	0.02	2.55	
		20%	24.08	2.32	55.80	4535	308.120	0.06	5.47	
		30%	24.00	5.02	120.40	6230	644.540	0.11	5.25	
		40%	23.93	9.78	233.80	7842	1089.618	0.18	4.76	
5215 2400KV	CR10X5X3	50%	23.79	15.28	411.10	9972	1663.829	0.27	3.95	✓
		60%	23.62	26.61	628.50	11458	2418.810	0.36	3.52	
		70%	23.48	37.46	879.00	12953	2913.590	0.46	3.30	
		80%	23.28	51.33	1194.84	13723	3434.450	0.52	2.89	
		90%	23.03	67.94	1564.40	14955	4049.290	0.67	2.57	
		100%	22.73	83.50	1898.00	15628	4536.520	0.76	2.39	

Motor	Propeller	Throttle	Voltage (V)	Current (A)	Power (W)	RPM	Thrust (g)	Torque (N*m)	Efficiency (g/W)	Temperature (°C)
		10%	48.05	0.22	10.40	1980	42.170	0.05	4.08	
		20%	48.02	0.73	34.90	3464	271.750	0.06	7.78	
		30%	48.01	1.77	85.00	5197	615.009	0.11	7.28	
		40%	47.98	3.33	159.80	6738	1048.068	0.15	6.56	
5215 1650KV	CR10X5X3	50%	47.93	5.79	325.00	8030	1645.000	0.29	5.13	✓
		60%	47.87	10.26	490.91	9825	2148.290	0.36	5.00	
		70%	47.80	15.08	744.20	10821	2592.940	0.51	3.84	
		80%	47.62	21.30	1134.60	11855	3153.230	0.62	3.30	
		90%	47.54	27.81	1495.10	13011	4088.958	0.76	2.91	
		100%	47.38	33.84	1982.40	13721	4817.580	0.85	2.43	
		10%	32.08	0.33	10.70	2126	31.120	0.03	2.91	
		20%	32.07	1.25	40.20	3686	284.810	0.05	7.05	
		30%	32.04	3.13	100.30	5241	693.410	0.11	6.54	
		40%	32.00	5.94	190.50	6958	1137.218	0.15	5.92	
5215 1400KV	CR10X5X3	50%	31.95	9.47	340.60	8950	1704.670	0.29	5.01	✓
		60%	31.83	16.50	525.20	9832	2211.850	0.38	4.22	
		70%	31.73	25.28	799.19	10603	2952.160	0.51	3.69	
		80%	31.55	34.25	1080.40	11732	3359.360	0.60	3.29	
		90%	31.28	47.53	1485.40	12990	4055.280	0.74	2.88	
		100%	31.17	61.81	1927.00	13662	4777.400	0.86	2.49	
		10%	24.04	0.50	12.10	3249	27.530	0.02	2.30	
		20%	24.02	1.66	39.70	3521	305.730	0.06	6.76	
		30%	23.99	4.54	108.60	5179	991.350	0.12	6.53	
		40%	23.80	8.36	229.80	6950	1374.950	0.20	5.42	
5215 1000KV	CR10X5X3	50%	23.79	15.86	377.30	8351	1759.890	0.29	4.72	✓
		60%	23.63	23.86	563.70	9916	2326.550	0.42	4.09	
		70%	23.49	36.07	847.30	11464	2993.530	0.52	3.53	
		80%	23.28	50.48	1175.10	13055	3845.530	0.82	3.11	
		90%	23.03	66.87	1539.80	13795	4244.910	0.94	2.76	
		100%	22.74	83.28	1894.20	15079	4113.290	0.80	2.50	
		10%	48.06	0.41	19.50	2598	82.190	0.04	4.23	
		20%	48.06	1.49	69.20	4551	458.630	0.09	6.64	
		30%	48.04	3.26	156.40	6098	1003.910	0.17	5.93	
		40%	47.99	6.32	293.50	7908	1565.950	0.27	5.34	
5215 650KV	CR10X5X3	50%	47.92	11.25	539.50	9851	2370.456	0.41	4.41	✓
		60%	47.82	18.18	870.00	11209	3226.600	0.56	3.71	
		70%	47.68	28.82	1290.48	12648	4123.670	0.72	3.25	
		80%	47.50	37.87	1798.50	13976	5094.840	0.90	2.85	
		90%	47.30	51.16	2418.70	15234	6113.710	1.09	2.51	
		100%	47.08	68.51	3245.00	16069	6837.990	1.23	2.11	
		10%	32.08	0.51	15.40	2111	52.160	0.03	3.52	
		20%	32.06	1.89	60.70	4206	388.290	0.08	6.46	
		30%	32.05	4.42	142.40	5586	865.030	0.14	6.08	
		40%	31.97	9.07	257.90	7294	1326.120	0.23	5.27	
5215 500KV	CR10X5X3	50%	31.80	13.88	440.10	8606	2043.230	0.35	4.85	✓
		60%	31.77	22.37	710.80	10353	2750.420	0.47	3.88	
		70%	31.65	33.84	1069.00	11771	3566.100	0.66	3.34	
		80%	31.44	44.84	1409.10	13009	4434.810	0.77	3.14	
		90%	31.20	59.97	1862.00	14150	5430.750	0.92	2.73	
		100%	30.89	76.43	2412.10	15106	6430.150	1.08	2.46	

Contents



Please check that your package contains all the above items before use. If something is missing, please contact online customer service or leave a message to

Zawartość:
1x C10.5x5.3 CW
1x C10.5x5.3 CCW