Dane aktualne na dzień: 24-11-2026 09:51

Link do produktu: https://www.nobshop.pl/smigla-t-motor-cine-8550-c85x53-1cw-1ccw-p-4444.html



Śmigła T-Motor Cine 8550 C8.5x5.3 1CW 1CCW

Cena brutto	**59,99 zł**
Cena netto	**48,77 zł**
Dostępność	**Dostępny**
Czas wysyłki	**1 - 3 dni**
Producent	**T-Motor**

Opis produktu

Śmigła T-Motor Cine 8550 C8.5x5.3 1CW 1CCW


LARGE THRUST
load weight 1-4kg, take-off weight 4-9kg no
pressure on loaded shooting equipment



SMALL
VIBRATION
Reasonable structural design
less power loss, and longer
flight time
TO THE FREEDOM


HIGH EFFICIENCY
The blades are not easily deformed
parameter adjustment is simple, perfect for
fpv cinematic



Specyfikacja:

Product Drawing



Specifications

Model	C8.5X5	Hub Diameter	16.4mm
Includes	1x CCW Prop 1x CW Prop	Center Thickness	4mm
Blades	5	Hub Inner Diameter	5mm
Material	Glass fiber nylon	Maximum blade width	21.7mm
Pitch	5in	Weight	14.8g
Prop Disc Diameter	216mm	Recommended Power Combo	CM4004 1100KV/PP5X5C 4S6.4MM

Model	C10.5X5	Hub Diameter	12.2mm
Includes	1x CCW Prop 1x CW Prop	Center Thickness	4mm
Blades	5	Hub Inner Diameter	5mm
Material	Glass fiber nylon	Maximum blade width	25.5mm
Pitch	5in	Weight	21.5g
Prop Disc Diameter	240mm	Recommended Power Combo	V3115 1000KV/PP5X5C 4S6 4M3

Model	C9.5X5	Hub Diameter	13.6mm
Includes	1x CCW Prop 1x CW Prop	Center Thickness	4mm
Blades	5	Hub Inner Diameter	5mm
Material	Glass fiber nylon	Maximum blade width	24.3mm
Pitch	5in	Weight	19.7g
Prop Disc Diameter	267mm	Recommended Power Combo	V3125 700KV/PP5X5C 4S6 4J5

Test Report

Motor	Propeller	Throttle	Voltage (V)	Current (A)	Power (W)	RPM	Thrust (g)	Torque (N*m)	Efficiency (g/W)	Temperature (°C)
		10%	24.07	0.73	17.60	2548	34.24	0.09	1.26	
		20%	24.08	2.66	64.40	3482	104.04	0.20	2.30	
		30%	24.00	5.53	132.80	3340	182.40	0.33	2.61	
		40%	23.92	9.30	222.50	3890	282.40	0.51	2.42	
5205/2 1150KV	CR1055X3	50%	23.83	14.24	339.40	4353	1423.258	0.67	3.68	✓
		60%	23.77	23.10	547.60	5194?	1914.800	0.89	3.50	
		70%	23.66	33.75	798.60	5728	2464.210	0.98	3.10	
		80%	23.59	45.54	1065.10	6490	2932.340	0.95	2.75	
		90%	23.48	59.21	1312.34	6696	3264.420	0.51	2.47	
		100%	23.97	72.58	1680.70	7230?	3892.578	0.60	2.25	
		10%	24.07	0.72	17.30	2458	34.256	0.05	4.95	
		20%	24.04	2.65	63.70	3306	266.870	0.06	5.90	
		30%	24.00	5.52	147.80	3332	656.996	0.11	5.45	
		40%	23.92	9.48	226.80	3717	1009.200	0.16	4.49	
CM4004 1150KV	CR1055X3	50%	23.83	14.14	384.30	4464	1434.660	0.22	4.73	✓
		60%	23.77	22.86	542.00	5202	1913.689	0.20	3.54	
		70%	23.67	33.62	774.30	5598	2446.540	0.28	3.16	
		80%	23.60	44.28	1026.20	6404	2932.980	0.45	2.82	
		90%	25.26	57.92	1366.70	6904	3366.660	0.51	2.52	
		100%	23.95	72.12	1657.90	7495	3857.768	0.60	2.30	
		10%	24.03	0.35	8.40	2427	42.088	0.04	7.41	
		20%	24.02	1.45	34.82	4705	232.160	0.04	7.23	
		30%	24.00	3.66	87.80	5661	552.360	0.09	6.29	
		40%	23.93	7.43	177.70	6870	955.720	0.14	5.38	
V3008 1115KV	CR1055X3	50%	23.83	12.41	307.80	7982	1542.588	0.21	5.11	✓
		60%	23.73	20.91	474.90	11153	1989.000	0.28	4.56	
		70%	23.57	30.54	719.80	12862	2435.160	0.36	3.64	
		80%	23.42	40.36	945.20	13859	2920.980	0.40	3.64	
		90%	25.22	54.33	1265.80	14623	2843.730	0.46	3.33	
		100%	23.82	68.42	1574.80	15092	3384.810	0.47	3.08	
		10%	24.05	0.33	7.80	2521	42.788	0.04	7.37	
		20%	24.02	1.35	32.30	4653	246.109	0.04	7.61	
		30%	23.99	3.38	79.50	5686	551.280	0.08	6.59	
		40%	23.94	6.98	167.50	8235	903.980	0.14	5.51	
F450 1130KV	CR1055X3	50%	23.83	11.66	277.00	9891	1595.580	0.20	4.62	✓
		60%	23.78	19.38	411.80	11207	1964.270	0.25	4.83	
		70%	23.62	28.13	617.50	13735	2430.420	0.33	3.93	
		80%	23.50	37.68	885.20	13298	2920.980	0.40	3.30	
		90%	25.18	51.83	1305.00	14078	3158.890	0.52	2.93	
		100%	23.93	57.88	1321.40	13935	3547.020	0.59	2.85	
		10%	24.05	0.51	7.90	2123	44.050	0.07	8.78	
		20%	24.02	1.53	31.80	3990	256.009	0.05	8.48	
		30%	23.99	3.28	78.80	5808	551.500	0.09	7.24	
		40%	23.95	6.99	170.90	7732	941.258	0.15	5.85	
CM4004 1050KV	CR1055X3	50%	23.88	10.93	261.30	8588	1320.430	0.23	5.06	✓
		60%	23.78	17.38	411.00	9864	1739.748	0.30	4.33	
		70%	23.65	24.99	590.80	11589	2252.360	0.37	3.82	
		80%	23.50	34.86	819.30	12792	2727.988	0.45	3.33	
		90%	25.35	45.18	1145.20	13062	3140.788	0.52	2.98	
		100%	23.93	56.01	134.230	13398	3545.259	0.59	2.78	
		10%	48.05	0.21	10.08	2134	44.940	0.02	4.49	
		20%	48.02	0.76	36.40	4401	272.889	0.05	7.53	
		30%	48.02	1.46	70.00	5412	476.648	0.08	6.82	
		40%	47.99	3.11	149.20	7301	893.578	0.14	5.74	
S2115 4000KV	CR1055X3	50%	47.93	5.51	264.40	8640	1320.320	0.22	4.92	✓
		60%	47.91	8.01	383.80	10409	1750.818	0.29	4.51	
		70%	47.85	12.15	581.50	11455	2237.550	0.39	3.83	
		80%	47.73	17.66	843.00	13860	2898.105	0.50	3.38	
		90%	47.80	23.77	1135.80	14933	3458.768	0.61	3.01	
		100%	47.54	31.42	1493.40	15255	4290.180	0.72	2.88	
		10%	32.08	0.33	10.60	3241	52.200	0.09	4.95	
		20%	32.07	1.21	38.90	4448	242.278	0.06	6.25	
		30%	32.04	2.64	84.60	5442	516.000	0.09	6.12	
		40%	32.01	5.01	160.40	7165	881.906	0.14	5.50	
S2115 5400KV	CR1055X3	50%	31.95	8.72	278.50	8132	1322.480	0.22	4.79	✓
		60%	31.88	12.83	409.40	9493	1767.458	0.30	4.33	
		70%	31.80	18.42	617.90	11334	2288.360	0.39	3.87	
		80%	31.82	23.77	874.40	12900	2815.006	0.50	3.45	
		90%	31.33	27.44	1138.50	14120	3417.148	0.60	3.08	
		100%	31.36	49.83	1522.60	15211	4270.560	0.71	2.78	
		10%	24.05	0.49	11.80	3264	29.430	0.02	2.50	
		20%	24.03	1.88	45.30	4251	246.406	0.05	5.42	
		30%	24.00	3.88	93.10	5795	541.440	0.13	5.88	
S2115 5400KV	CR1055X3	40%	23.96	7.48	177.50	7631	942.988	0.16	5.27	
		50%	23.94	12.53	299.30	8930	1402.560	0.23	4.69	✓
		60%	23.92	18.68	446.70	10068	1901.758	0.32	4.08	
		70%	23.80	28.85	680.80	11723	2470.640	0.41	3.64	
		80%	23.65	40.01	951.30	13606	3083.446	0.53	3.24	
		90%	25.03	54.17	1237.00	14176	3462.898	0.61	2.91	
		100%	23.98	70.81	1698.90	15190	4240.056	0.73	2.64	
		10%	24.06	0.63	15.70	3731	29.900	0.02	2.55	
		20%	24.08	2.32	55.80	4535	308.120	0.06	5.47	
		30%	24.00	5.02	120.40	6230	644.540	0.11	5.25	
S2115 5400KV	CR1055X3	40%	23.93	9.78	233.80	7842	1089.618	0.18	4.76	
		50%	23.79	15.28	413.10	9972	1663.829	0.27	3.95	✓
		60%	23.82	20.61	529.00	11458	2010.818	0.36	3.52	
		70%	23.48	31.46	879.00	13953	2913.598	0.46	3.30	
		80%	25.28	51.33	1158.00	17233	3656.050	0.52	2.89	
		90%	23.93	67.94	1564.40	19705	4604.298	0.87	2.57	
		100%	22.73	83.50	1898.00	19658	4556.520	0.76	2.39	
Motor	Propeller	Throttle	Voltage (V)	Current (A)	Power (W)	RPM	Thrust (g)	Torque (N*m)	Efficiency (g/W)	Temperature (°C)
		10%	48.05	0.22	10.40	1980	42.170	0.05	4.08	
		20%	48.02	0.73	34.90	3464	271.750	0.06	7.78	
		30%	48.01	1.77	85.00	5197	615.009	0.11	7.28	
		40%	47.98	3.33	159.80	6258	1048.068	0.15	6.56	
S2115 5400KV	CR1055X3	50%	47.93	5.79	277.50	8030	1645.660	0.29	5.13	✓
		60%	47.87	10.26	490.95	9825	2148.290	0.36	5.00	
		70%	47.80	15.08	744.20	10821	2592.948	0.51	3.84	
		80%	47.62	21.30	1134.60	11855	3153.230	0.62	3.30	
		90%	47.54	27.81	1495.10	13011	4008.958	0.74	2.91	
		100%	47.58	33.84	1982.40	13721	4817.588	0.85	2.43	
		10%	32.08	0.33	10.70	3128	37.135	0.03	3.45	
		20%	32.07	1.25	40.20	5086	284.810	0.06	7.05	
		30%	32.04	2.72	100.30	5241	693.410	0.11	6.54	
S2115 5400KV	CR1055X3	40%	32.00	5.06	156.50	6356	1137.218	0.15	5.92	
		50%	31.95	10.67	340.90	8950	1958.678	0.29	5.81	✓
		60%	31.85	16.50	525.20	9832	2317.858	0.38	4.23	
		70%	31.73	25.28	799.19	10603	2952.168	0.51	3.69	
		80%	31.55	34.25	1080.40	11732	3358.360	0.60	3.29	
		90%	31.68	47.53	1505.40	12990	4093.388	0.91	2.66	
		100%	31.37	61.81	1927.00	13662	4777.488	0.86	2.49	
		10%	24.04	0.59	12.70	3245	27.595	0.02	2.18	
		20%	24.02	1.66	35.10	3727	305.730	0.06	8.76	
		30%	23.99	4.54	108.60	5179	991.350	0.12	9.13	
		40%	23.80	8.26	229.80	6950	1374.990	0.20	5.82	
S2115 5400KV	CR1055X3	50%	23.79	15.86	377.30	8351	1759.898	0.29	4.72	✓
		60%	23.63	23.86	563.70	9516	2326.030	0.42	4.09	
		70%	23.49	36.07	847.30	11464	3043.528	0.52	3.53	
		80%	23.28	50.48	1175.00	13055	3845.530	0.82	3.11	
		90%	23.05	66.87	1540.80	13795	4244.918	0.94	2.70	
		100%	22.79	83.28	1896.20	15079	4733.298	0.80	2.50	
		10%	48.06	0.41	19.50	2598	82.190	0.04	4.23	
		20%	48.06	1.49	69.20	4551	458.638	0.09	6.64	
		30%	48.04	3.26	156.40	6098	1003.910	0.17	6.42	
		40%	47.99	6.32	293.50	7908	1565.950	0.27	5.34	
S2120 5200KV	CR1055X3	50%	47.92	11.25	539.50	9851	2370.458	0.49	4.41	✓
		60%	47.82	18.18	870.00	11209	3226.600	0.56	3.71	
		70%	47.68	28.82	1290.48	12648	4123.978	0.72	3.25	
		80%	47.50	37.87	1798.50	13976	5094.845	0.90	2.85	
		90%	47.30	51.56	2438.70	15234	6113.718	1.09	2.51	
		100%	47.08	68.51	3345.00	16069	6837.948	1.23	2.11	
		10%	32.08	0.51	15.40	2111	52.160	0.03	3.52	
		20%	32.06	1.89	60.70	4206	388.298	0.08	6.48	
		30%	32.05	4.10	132.30	5586	865.038	0.14	6.68	
		40%	31.97	9.87	257.90	7294	1539.320	0.25	5.27	
S2120 700KV	CR1055X3	50%	31.80	15.68	448.50	8606	2443.258	0.35	4.85	✓
		60%	31.77	22.37	713.30	10353	3758.420	0.47	3.88	
		70%	31.65	33.66	1080.00	11771	5566.188	0.66	3.50	
		80%	31.44	44.84	1490.10	13009	7459.818	0.77	3.14	
		90%	31.20	58.97	1902.00	14150	9436.758	0.92	2.73	
		100%	30.89	76.43	2412.10	15106	10830.150	1.08	2.46	

Contents



Please check that your package contains all the above items before use. If something is missing, please contact online customer service or leave message to sales@tmotor.com

Zawartość:
1x C8.5x5.3 CW
1x C8.5x5.3 CCW