Dane aktualne na dzień: 25-11-2026 14:07

Link do produktu: https://www.nobshop.pl/smigla-t-motor-cine-9550-c95x53-1cw-1ccw-p-4382.html



Śmigła T-Motor Cine 9550 C9.5x5.3 1CW 1CCW


Cena brutto	**64,99 zł**
Cena netto	**52,84 zł**
Dostępność	**Dostępny**
Czas wysyłki	**1 - 3 dni**
Producent	**T-Motor**

Opis produktu

Śmigła T-Motor 9550 C9.5x5.3 1CW 1CCW

Specyfikacja:

Product Drawing



Specifications

Model	C8.5X5	Hub Diameter	16.4mm
Includes	1x CCW Prop 1x CW Prop	Center Thickness	4mm
Blades	5	Hub Inner Diameter	5mm
Material	Glass fiber nylon	Maximum blade width	21.7mm
Pitch	5in	Weight	14.8g
Prop Disc Diameter	216mm	Recommended Power Combo	CM4004 1100KV/PP5X5C 4S6.4MM

Model	C10.5X5	Hub Diameter	12.2mm
Includes	1x CCW Prop 1x CW Prop	Center Thickness	4mm
Blades	5	Hub Inner Diameter	5mm
Material	Glass fiber nylon	Maximum blade width	25.5mm
Pitch	5in	Weight	21.5g
Prop Disc Diameter	240mm	Recommended Power Combo	V3115 1000KV/PP5X5C 4S6 4M3

Model	C9.5X5	Hub Diameter	13.6mm
Includes	1x CCW Prop 1x CW Prop	Center Thickness	4mm
Blades	5	Hub Inner Diameter	5mm
Material	Glass fiber nylon	Maximum blade width	24.3mm
Pitch	5in	Weight	19.7g
Prop Disc Diameter	267mm	Recommended Power Combo	V3125 500KV/PP5X5C 4S6 4Z5

Test Report

Motor	Propeller	Throttle	Voltage (V)	Current (A)	Power (W)	RPM	Thrust (g)	Torque (N*m)	Efficiency (g/W)	Temperature (°C)
		10%	24.07	0.73	17.60	2540	34.14	0.09	1.26	
		20%	24.08	2.66	64.42	3492	134.50	0.30	2.30	
		30%	24.00	5.53	132.82	3340	302.40	0.45	2.61	
		40%	23.92	9.30	222.50	3890	382.40	0.72	2.45	
5205/2 1150KV	CR10X5X3	50%	23.89	14.24	340.40	4353	1425.20	0.97	3.08	✓
		60%	23.77	23.18	547.60	5194?	1914.800	0.29	3.50	
		70%	23.82	33.75	794.00	5728	2464.210	0.38	3.10	
		80%	23.39	45.54	1065.10	6080	2932.340	0.45	2.75	
		90%	23.43	59.21	1312.34	6696	3324.420	0.53	2.47	
		100%	22.97	72.58	1668.70	7230	3892.570	0.60	2.25	
		10%	24.07	0.72	17.30	2458	34.250	0.05	4.95	
		20%	24.04	2.63	63.15	3306	266.010	0.06	5.00	
		30%	24.00	5.32	127.80	3332	656.990	0.11	5.25	
		40%	23.92	9.48	226.80	3717	1009.100	0.16	4.49	
CM4004 1150KV	CR10X5X3	50%	23.84	14.14	336.50	4464	1434.660	0.22	4.73	✓
		60%	23.77	22.86	542.00	5302	1953.690	0.30	3.54	
		70%	23.57	33.82	774.30	5998	2446.540	0.38	3.16	
		80%	23.40	44.28	1036.20	6604	2932.980	0.45	2.82	
		90%	23.26	57.92	1346.70	7204	3466.660	0.53	2.52	
		100%	22.95	72.12	1655.40	7695	3857.760	0.60	2.30	
		10%	24.03	0.35	8.40	2427	42.080	0.04	7.41	
		20%	24.02	1.45	34.82	4705	232.160	0.04	7.23	
		30%	24.00	3.66	87.80	5661	552.360	0.09	6.29	
		40%	23.93	7.43	177.70	6870	955.720	0.14	5.18	
5108B 1150KV	CR10X5X3	50%	23.85	12.41	297.80	7982	1542.580	0.23	5.13	✓
		60%	23.73	20.91	496.90	11153	1989.090	0.28	4.56	
		70%	23.57	30.54	719.80	12862	2435.160	0.36	3.84	
		80%	23.42	40.36	945.20	13879	2920.980	0.40	3.64	
		90%	23.22	54.33	1261.80	14623	2843.730	0.46	2.53	
		100%	23.02	68.42	1574.80	15292	3389.810	0.49	2.58	
		10%	24.05	0.33	7.80	2521	42.700	0.04	5.37	
		20%	24.02	1.35	32.30	4632	246.120	0.04	7.61	
		30%	23.99	3.38	79.50	5686	551.280	0.08	6.59	
		40%	23.94	6.98	167.10	6870	955.980	0.14	5.51	
F405 1100KV	CR10X5X3	50%	23.87	11.66	277.00	7891	1545.160	0.20	4.62	✓
		60%	23.78	19.38	411.80	11207	1964.270	0.25	4.83	
		70%	23.62	28.13	617.50	12731	2430.420	0.33	3.65	
		80%	23.47	37.38	877.30	13879	2920.980	0.40	3.33	
		90%	23.23	50.85	1181.30	14623	2843.730	0.46	2.41	
		100%	23.03	63.89	1471.70	15296	3389.540	0.54	2.30	

Motor	Propeller	Throttle	Voltage (V)	Current (A)	Power (W)	RPM	Thrust (g)	Torque (N*m)	Efficiency (g/W)	Temperature (°C)
		10%	24.05	0.36	8.61	2162	36.210	0.05	7.25	
		20%	24.03	1.53	31.80	4053	250.030	0.05	7.87	
		30%	23.99	4.16	75.50	5663	551.640	0.09	7.08	
		40%	23.95	8.19	148.00	7198	887.610	0.15	5.99	
5205/2 970KV	CR10X5X3	50%	23.88	16.81	258.00	8846	1373.350	0.23	4.96	✓
		60%	23.78	27.54	411.00	9915	1789.880	0.29	4.27	
		70%	23.65	39.50	579.30	11121	2190.360	0.32	3.78	
		80%	23.50	51.88	804.20	12368	2750.980	0.45	3.35	
		90%	23.35	65.53	1060.00	13070	3138.890	0.52	2.93	
		100%	23.10	77.99	1323.40	13595	3543.020	0.59	2.65	
		10%	24.05	0.51	7.90	2323	44.050	0.07	8.78	
		20%	24.02	1.53	31.80	3998	256.030	0.05	8.48	
		30%	23.99	4.16	74.90	5606	551.500	0.09	7.24	
		40%	23.95	8.18	150.90	7132	941.250	0.15	6.05	
CM4004 970KV	CR10X5X3	50%	23.88	16.93	261.50	8588	1320.430	0.23	5.06	✓
		60%	23.78	27.38	411.00	9844	1739.740	0.30	4.23	
		70%	23.65	39.99	590.80	11089	2252.360	0.37	3.82	
		80%	23.50	54.86	815.30	12192	2727.980	0.45	3.33	
		90%	23.35	65.18	1055.20	13062	3140.780	0.52	2.98	
		100%	23.10	78.01	1241.50	13595	3543.250	0.59	2.78	
		10%	48.05	0.21	10.08	2134	34.940	0.02	3.49	
		20%	48.02	0.76	35.40	4451	272.889	0.05	7.53	
		30%	48.02	1.46	70.00	5412	470.430	0.08	6.82	
		40%	47.99	3.11	149.20	7101	893.576	0.14	5.74	
5215 4000KV	CR10X5X3	50%	47.93	5.51	264.40	8442	1320.320	0.22	4.92	✓
		60%	47.91	8.01	412.30	10409	1750.810	0.29	4.21	
		70%	47.83	12.15	581.30	11455	2237.550	0.39	3.83	
		80%	47.73	17.46	833.80	12860	2686.330	0.50	3.18	
		90%	47.60	23.77	1131.00	14111	3448.710	0.61	3.01	
		100%	47.54	31.42	1465.40	15255	4290.180	0.72	2.88	
		10%	32.08	0.33	9.68	2041	32.200	0.03	3.05	
		20%	32.07	1.21	36.90	4448	242.278	0.04	6.25	
		30%	32.04	3.04	94.61	5943	516.000	0.09	6.72	
		40%	32.01	5.81	190.80	7765	881.906	0.14	5.56	
5215 3400KV	CR10X5X3	50%	31.96	9.72	278.50	9132	1323.480	0.22	4.79	✓
		60%	31.88	13.84	441.40	10972	1767.450	0.30	4.15	
		70%	31.80	18.42	617.90	11554	2288.360	0.39	3.87	
		80%	31.82	23.77	874.40	12900	2813.000	0.50	3.45	
		90%	31.33	27.44	1138.50	14120	3437.140	0.60	3.08	
		100%	31.36	49.83	1522.60	15211	4270.560	0.71	2.78	
		10%	24.05	0.49	11.80	3264	29.430	0.02	2.50	
		20%	24.03	1.88	45.30	4251	246.300	0.05	5.42	
		30%	24.00	3.88	93.10	5790	541.440	0.13	5.88	
		40%	23.96	7.48	177.50	7631	942.900	0.16	5.27	
5215 3000KV	CR10X5X3	50%	23.94	12.53	299.30	8930	1402.560	0.23	4.69	✓
		60%	23.52	20.83	489.70	10468	1903.730	0.32	3.88	
		70%	23.80	28.85	680.80	11723	2470.640	0.41	3.64	
		80%	23.63	40.01	951.30	13006	3083.880	0.53	3.24	
		90%	23.43	54.17	1257.80	14156	3962.890	0.61	2.91	
		100%	23.08	70.01	1608.90	15190	4240.050	0.73	2.64	
		10%	24.06	0.63	15.70	3721	29.900	0.02	2.55	
		20%	24.08	2.32	55.80	4535	308.120	0.06	5.47	
		30%	24.00	5.02	120.40	6230	644.540	0.11	5.25	
		40%	23.93	9.78	233.80	7842	1089.618	0.18	4.76	
5215 2400KV	CR10X5X3	50%	23.79	15.28	411.10	9972	1663.829	0.27	3.95	✓
		60%	23.62	26.61	628.50	11458	2418.810	0.36	3.52	
		70%	23.48	37.46	879.00	12953	2913.590	0.46	3.30	
		80%	23.28	51.33	1194.84	13723	3434.450	0.52	2.89	
		90%	23.03	67.94	1564.40	14955	4049.290	0.67	2.57	
		100%	22.73	83.50	1898.00	15628	4536.520	0.76	2.39	

Motor	Propeller	Throttle	Voltage (V)	Current (A)	Power (W)	RPM	Thrust (g)	Torque (N*m)	Efficiency (g/W)	Temperature (°C)
		10%	48.05	0.22	10.40	1980	42.170	0.05	4.08	
		20%	48.02	0.73	34.90	3464	271.750	0.06	7.78	
		30%	48.01	1.77	85.00	5197	615.009	0.11	7.28	
		40%	47.98	3.33	159.80	6738	1048.068	0.15	6.56	
5215 1650KV	CR10X5X3	50%	47.93	5.79	325.00	8030	1645.000	0.29	5.13	✓
		60%	47.87	10.26	490.91	9825	2148.290	0.36	5.00	
		70%	47.80	15.08	744.20	10821	2592.940	0.51	3.84	
		80%	47.62	21.30	1134.60	11855	3153.230	0.62	3.30	
		90%	47.54	27.81	1495.10	13011	4088.958	0.76	2.91	
		100%	47.38	33.84	1982.40	13721	4817.580	0.85	2.43	
		10%	32.08	0.33	10.70	2126	31.120	0.03	2.91	
		20%	32.07	1.25	40.20	3686	284.810	0.05	7.05	
		30%	32.04	3.13	100.30	5241	693.410	0.11	6.54	
		40%	32.00	5.94	190.50	6958	1137.218	0.15	5.92	
5215 1400KV	CR10X5X3	50%	31.95	9.47	340.60	8950	1704.670	0.29	5.01	✓
		60%	31.83	16.50	525.20	9832	2211.850	0.38	4.22	
		70%	31.73	25.28	799.19	10603	2952.160	0.51	3.69	
		80%	31.55	34.25	1080.40	11732	3359.360	0.60	3.29	
		90%	31.28	47.53	1485.40	12990	4093.280	0.74	2.86	
		100%	31.17	61.81	1927.00	13662	4777.480	0.86	2.49	
		10%	24.04	0.50	12.10	3249	27.530	0.02	2.30	
		20%	24.02	1.66	39.70	3727	305.730	0.06	7.76	
		30%	23.99	4.54	108.60	5179	991.350	0.12	9.13	
		40%	23.80	8.26	229.80	6950	1374.950	0.20	5.98	
5215 1000KV	CR10X5X3	50%	23.79	15.86	377.30	8351	1759.890	0.29	4.72	✓
		60%	23.63	23.86	563.70	9916	2326.550	0.40	4.09	
		70%	23.49	36.07	847.30	11464	2993.530	0.52	3.53	
		80%	23.28	50.48	1175.10	13055	3845.530	0.82	3.11	
		90%	23.03	66.87	1539.80	13795	4244.910	0.94	2.76	
		100%	22.74	83.28	1894.20	15079	4733.290	0.80	2.50	
		10%	48.06	0.41	19.50	2598	82.190	0.04	4.23	
		20%	48.06	1.49	69.20	4551	458.630	0.09	6.64	
		30%	48.04	3.26	156.40	6098	1003.910	0.17	6.42	
		40%	47.99	6.32	293.50	7908	1565.950	0.27	5.34	
5215 650KV	CR10X5X3	50%	47.92	11.25	539.50	9851	2370.456	0.41	4.41	✓
		60%	47.82	18.18	870.00	11209	3226.600	0.56	3.71	
		70%	47.68	28.82	1290.48	12648	4123.670	0.72	3.25	
		80%	47.50	37.87	1798.50	13976	5094.840	0.90	2.85	
		90%	47.30	51.56	2438.70	15234	6113.710	1.09	2.51	
		100%	47.08	68.51	3245.20	16069	6837.990	1.23	2.11	
		10%	32.08	0.51	15.40	2111	52.160	0.03	3.52	
		20%	32.06	1.89	58.70	4236	388.290	0.08	6.46	
		30%	32.05	4.42	142.40	5586	865.030	0.14	6.08	
		40%	31.97	9.07	257.90	7294	1326.120	0.23	5.27	
5215 500KV	CR10X5X3	50%	31.80	13.68	449.10	8606	2043.258	0.35	4.85	✓
		60%	31.77	22.37	715.80	10353	2758.420	0.47	3.98	
		70%	31.65	33.84	1080.60	11771	3566.180	0.66	3.30	
		80%	31.44	44.84	1490.10	13009	4434.810	0.77	3.14	
		90%	31.20	59.97	1902.00	14150	5436.750	0.92	2.73	
		100%	30.89	76.43	2412.10	15106	6430.150	1.08	2.46	

Contents



Please check that your package contains all the above items before use. If something is missing, please contact online customer service or leave a message to

Zawartość:
1x C9.5x5.3 CW
1x C9.5x5.3 CCW