

Link do produktu: <https://www.nobshop.pl/stack-geprc-f722-bt-8bit-60a-p-5023.html>

Stack GepRC F722 BT 8Bit 60A



Cena brutto	304,99 zł
Cena netto	247,96 zł
Dostępność	Dostępny
Czas wysyłki	1 - 3 dni
Kod producenta	GP107549
Producent	GepRC

Opis produktu

Stack GepRC F722 BT 8Bit 60A

Features

1. Use mainstream STM32F722 chip
2. Equipped with the latest 42688-P gyroscope
3. 512M black box storage
4. Support Bluetooth parameter tuning
5. Integrated LC filter
6. Upgrade type-C USB interface
7. With TAKER H60_BLS 60A 4IN1 ESC, silky flight
8. Directly plugs into the DJI Air Unit
9. Simple and effective installation with shock-absorbing mounts for stable gyroscope performance
10. Integrated Barometer
11. 9V@2.5A + 5V@3A dual independent BEC

Specifications

GEP-F722-BT-HD V3 Flight Controller

- MCU: STM32F722
- IMU: ICM42688-P(SPI)
- Air Unit Connection: Directly plugs into the DJI Air Unit
- Black Box: 512M onboard
- Bluetooth: Supported
- Barometer: Supported
- USB Interface: Type-C
- OSD: BetaFlight OSD w/ AT7456E chip
- BEC: 5V@3A, 9V@2.5A dual BEC
- Firmware Target: GEPRCF722_BT_HD_V3
- Size: 36.9×36.9mm, hole: 30.5×30.5mm, \varnothing 4mm hole becomes \varnothing 3mm after using a silicone shock-absorbing ring
- Input Voltage: 3-6S LiPo

-
- UART: 5 groups (UART4 fixed for Bluetooth)
 - Power Filter: Integrated LC filter
 - Weight: 8.2g

TAKER H60_BLS 60A 4IN1 ESC

- Input Voltage: 3-6S Lipo
- Ammeter: Support
- Continue Current[]60A
- Burst Current: 65A (5 second)
- Support Protocol: Dshot 150/300/600
- Size: 42×45.7mm, hole: 30.5×30.5mm, \varnothing 4mm hole becomes \varnothing 3mm after using the silicone shock-absorbing ring
- Weight: 14.9g
- Target: B_X_30

Includes

- 1 x FC board
- 1 x ESC board
- 1 x Capacitor
- 1 x O3 3-in-1 connection cable
- 1 x FC adapter cable
- 1 x sh1.0 4pin silicone cable
- 1 x Camera connection cable
- 1 x VTX connection cable
- 1 x XT90 power cable
- 4 x M3*30 screws
- 4 x M3*25 screws
- 8 x Nylon nuts
- 12 x Silicone anti-shake pads