

Link do produktu: <https://www.nobshop.pl/system-transmisji-obrazu-dji-transmission-z-ekranem-p-3318.html>



System transmisji obrazu DJI Transmission z ekranem

Cena brutto	11 499,99 zł
Cena netto	9 349,59 zł
Dostępność	Dostępny
Czas wysyłki	1 - 3 dni
Producent	DJI

Opis produktu

Specifications

- **Weight**
 - Video Transmitter Weight: Approx. 350 g / 0.77 lbs (excluding antennas)
 - High-Bright Remote Monitor Weight: Approx. 727 g / 1.6 lbs (excluding antennas)
- **Dimensions**
 - Video Transmitter: 127×87×26 mm (L×W×H, excluding antennas)
 - High-Bright Remote Monitor: 213×135×51 mm (L×W×H, excluding antennas)
- **Operating Frequency**
 - Non DFS Frequency Band:
 - 2.4000-2.4835 GHz
 - 5.150-5.250 GHz
 - 5.725-5.850 GHz
 - DFS Frequency Band:
 - 5.250-5.350 GHz
 - 5.470-5.600 GHz
 - 5.650-5.725 GHz"
- **Transmitter Power (EIRP)**
 - 2.4000-2.4835 GHz:
 - <33 dBm (FCC)
 - <20 dBm (SRRC/CE/MIC)
 - 5.150-5.250 GHz:
 - <23 dBm (FCC/SRRC/MIC)
 - 5.250-5.350 GHz:

<30 dBm (FCC)
<23 dBm (SRRC/MIC)

5.470-5.600 GHz, 5.650-5.725 GHz:
<30 dBm (FCC)
<23 dBm (CE/MIC)

5.725-5.850 GHz:
<33 dBm (FCC/SRRC)
<14 dBm (CE)

- **Max Bandwidth**

- 40 MHz

- **Max Bitrate**

- 50 Mbps

- **Power Consumption**

- 11 W

- **Power Supply Voltage**

- 6 to 18 V

- **Output Voltage**

- Power Output Port: 6 to 18 V

- **Operating Time**

- Video Transmitter: 3 hours 40 minutes ^[1]
High-Bright Remote Monitor: 2 hours ^[1]

- **Input Video Format**

- 3G SDI: YCbCr 4:2:2 10-bit
HDMI RGB 4:4:4
1080p: 23.98/24/25/29.97/30/50/59.94/60fps
1080i: 50/59.94/60fps
720p: 50/59.94/60fps

- **Output Video Format**

- 3G SDI: YCbCr 4:2:2 10-bit
1080p: 23.98/24/25/29.97/30/50/59.94/60fps
1080i: 50/59.94/60fps
720p: 50/59.94/60fps

- **Input Audio Format**

- SDI embedded, HDMI embedded

- **Output Audio Format**

- PCM

- **Video Transmission System**

- O3 Pro

- **Max Video Bitrate**

- 50 Mbps

- **Video Transmission Latency**

- 68 ms ^[2]
100 ms ^[3]

- **Video Coding Format**

- H.264

- **Max Transmission Distance**

- 6 km (FCC) ^[4]
4 km (CE/SRRC/MIC) ^[4]

- **Max Bandwidth**

- 40 MHz

- **Operating Temperature**

- -10° to 45° C (14° to 113° F)

- **Mirror Control Mode Supported Camera Models**

- ZV1/A7 III/A7S III/A7M III/A7R III/A7R IV/A7 IV/FX3/A7S II/A6600/A6400 and all Sony cameras that support BRAVIA (HDMI control).

Other

- **Notes**

- 1. Measured at room temperature (25° C/77° F) with a fully charged WB37 battery.
2. Measured when shooting 1080p/60fps video.
3. Measured when shooting 1080p/24fps video.
4. In open environments free of obstructions or interference.