Dane aktualne na dzień: 04-11-2026 13:43

Link do produktu: https://www.nobshop.pl/system-transmisji-obrazu-dji-transmission-z-ekranem-p-3318.html



System transmisji obrazu DJI Transmission z ekranem

Cena brutto	**10 900,00 zł**
Cena netto	**8 861,79 zł**
Cena poprzednia	~~**11 499,99 zł**~~
Dostępność	**Dostępny**
Czas wysyłki	**1 - 3 dni**
Producent	**DJI**

Opis produktu

Specifications

- **Weight**
- Video Transmitter Weight: Approx. 350 g / 0.77 lbs (excluding antennas)
  High-Bright Remote Monitor Weight: Approx. 727 g / 1.6 lbs (excluding antennas)

- **Dimensions**
- Video Transmitter: 127×87×26 mm (L×W×H, excluding antennas)
  High-Bright Remote Monitor: 213×135×51 mm (L×W×H, excluding antennas)

- **Operating Frequency**
- Non DFS Frequency Band:
  2.4000-2.4835 GHz
  5.150-5.250 GHz
  5.725-5.850 GHz

  DFS Frequency Band:
  5.250-5.350 GHz
  5.470-5.600 GHz
  5.650-5.725 GHz"

- **Transmitter Power (EIRP)**
- 2.4000-2.4835 GHz:
  <33 dBm (FCC)
  <20 dBm (SRRC/CE/MIC)

  5.150-5.250 GHz:
  <23 dBm (FCC/SRRC/MIC)

5.250-5.350 GHz:
<30 dBm (FCC)
<23 dBm (SRRC/MIC)

5.470-5.600 GHz, 5.650-5.725 GHz:
<30 dBm (FCC)
<23 dBm (CE/MIC)

5.725-5.850 GHz:
<33 dBm (FCC/SRRC)
<14 dBm (CE)

- **Max Bandwidth**
- 40 MHz

- **Max Bitrate**
- 50 Mbps

- **Power Consumption**
- 11 W

- **Power Supply Voltage**
- 6 to 18 V

- **Output Voltage**
- Power Output Port: 6 to 18 V

- **Operating Time**
- Video Transmitter: 3 hours 40 minutes [1]
  High-Bright Remote Monitor: 2 hours [1]

- **Input Video Format**
- 3G SDI: YCbCr 4:2:2 10-bit
  HDMI RGB 4:4:4
  1080p: 23.98/24/25/29.97/30/50/59.94/60fps
  1080i: 50/59.94/60fps
  720p: 50/59.94/60fps

- **Output Video Format**
- 3G SDI: YCbCr 4:2:2 10-bit
  1080p: 23.98/24/25/29.97/30/50/59.94/60fps
  1080i: 50/59.94/60fps
  720p: 50/59.94/60fps

- **Input Audio Format**

- SDI embedded, HDMI embedded

- **Output Audio Format**
- PCM

- **Video Transmission System**
- O3 Pro

- **Max Video Bitrate**
- 50 Mbps

- **Video Transmission Latency**
- 68 ms [2]
  100 ms [3]

- **Video Coding Format**
- H.264

- **Max Transmission Distance**
- 6 km (FCC) [4]
  4 km (CE/SRRC/MIC) [4]

- **Max Bandwidth**
- 40 MHz

- **Operating Temperature**
- -10° to 45° C (14° to 113° F)

- **Mirror Control Mode Supported Camera Models**
- ZV1/A7 III/A7S III/A7M III/A7R III/A7R IV/A7 IV/FX3/A7S II/A6600/A6400 and all Sony cameras that support BRAVIA (HDMI control).

Other

- **Notes**
- 1. Measured at room temperature (25° C/77° F) with a fully charged WB37 battery.
  2. Measured when shooting 1080p/60fps video.
  3. Measured when shooting 1080p/24fps video.
  4. In open environments free of obstructions or interference.