

Link do produktu: <https://www.nobshop.pl/system-transmisji-obrazu-dji-transmission-z-ekranem-p-3318.html>

## System transmisji obrazu DJI Transmission z ekranem



Cena brutto	<b>10 900,00 zł</b>
Cena netto	<b>8 861,79 zł</b>
Cena poprzednia	<b>11 499,99 zł</b>
Dostępność	<b>Dostępny</b>
Czas wysyłki	<b>1 - 3 dni</b>
Producent	<b>DJI</b>

### Opis produktu

#### Specifications

- **Weight**
  - Video Transmitter Weight: Approx. 350 g / 0.77 lbs (excluding antennas)
  - High-Bright Remote Monitor Weight: Approx. 727 g / 1.6 lbs (excluding antennas)
- **Dimensions**
  - Video Transmitter: 127×87×26 mm (L×W×H, excluding antennas)
  - High-Bright Remote Monitor: 213×135×51 mm (L×W×H, excluding antennas)
- **Operating Frequency**
  - Non DFS Frequency Band:
    - 2.4000-2.4835 GHz
    - 5.150-5.250 GHz
    - 5.725-5.850 GHz
  - DFS Frequency Band:
    - 5.250-5.350 GHz
    - 5.470-5.600 GHz
    - 5.650-5.725 GHz"
- **Transmitter Power (EIRP)**
  - 2.4000-2.4835 GHz:
    - <33 dBm (FCC)
    - <20 dBm (SRRC/CE/MIC)
  - 5.150-5.250 GHz:
    - <23 dBm (FCC/SRRC/MIC)

---

5.250-5.350 GHz:  
<30 dBm (FCC)  
<23 dBm (SRRC/MIC)

5.470-5.600 GHz, 5.650-5.725 GHz:  
<30 dBm (FCC)  
<23 dBm (CE/MIC)

5.725-5.850 GHz:  
<33 dBm (FCC/SRRC)  
<14 dBm (CE)

- **Max Bandwidth**

- 40 MHz

- **Max Bitrate**

- 50 Mbps

- **Power Consumption**

- 11 W

- **Power Supply Voltage**

- 6 to 18 V

- **Output Voltage**

- Power Output Port: 6 to 18 V

- **Operating Time**

- Video Transmitter: 3 hours 40 minutes <sup>[1]</sup>  
High-Bright Remote Monitor: 2 hours <sup>[1]</sup>

- **Input Video Format**

- 3G SDI: YCbCr 4:2:2 10-bit  
HDMI RGB 4:4:4  
1080p: 23.98/24/25/29.97/30/50/59.94/60fps  
1080i: 50/59.94/60fps  
720p: 50/59.94/60fps

- **Output Video Format**

- 3G SDI: YCbCr 4:2:2 10-bit  
1080p: 23.98/24/25/29.97/30/50/59.94/60fps  
1080i: 50/59.94/60fps  
720p: 50/59.94/60fps

- **Input Audio Format**

- 
- SDI embedded, HDMI embedded
  - **Output Audio Format**
    - PCM
  - **Video Transmission System**
    - O3 Pro
  - **Max Video Bitrate**
    - 50 Mbps
  - **Video Transmission Latency**
    - 68 ms <sup>[2]</sup>
    - 100 ms <sup>[3]</sup>
  - **Video Coding Format**
    - H.264
  - **Max Transmission Distance**
    - 6 km (FCC) <sup>[4]</sup>
    - 4 km (CE/SRRC/MIC) <sup>[4]</sup>
  - **Max Bandwidth**
    - 40 MHz
  - **Operating Temperature**
    - -10° to 45° C (14° to 113° F)
  - **Mirror Control Mode Supported Camera Models**
    - ZV1/A7 III/A7S III/A7M III/A7R III/A7R IV/A7 IV/FX3/A7S II/A6600/A6400 and all Sony cameras that support BRAVIA (HDMI control).

## Other

- **Notes**
  1. Measured at room temperature (25° C/77° F) with a fully charged WB37 battery.
  2. Measured when shooting 1080p/60fps video.
  3. Measured when shooting 1080p/24fps video.
  4. In open environments free of obstructions or interference.

