Dane aktualne na dzień: 25-11-2026 04:59

Link do produktu: https://www.nobshop.pl/walksnail-avatar-moonlight-kit-air-unit-vtx-kamera-4k-p-4274.html



Walksnail AVATAR Moonlight kit Air Unit VTX + KAMERA 4K

Cena brutto	**829,99 zł**
Cena netto	**674,79 zł**
Dostępność	**Aktualnie niedostępny**
Czas wysyłki	**1 - 3 dni**
Kod producenta	**WN11-4K14B**
Producent	**Caddx FPV**

Opis produktu

features

●4k/60FPS
●Built-in EIS
●Sd card
●Dual Antennas
●Startlight Camera
●Support Gyroflow
●FOV 160°
●7.4V-25.2V

Bullet Points:

- Supports 4K/60fps, ensuring that FPV embraces true 4K. Shooting stable and HD videos without unnecessary latency, bring pilots a smoother FPV experience.
- Feature starlight sensor, to improve image quality and performance in low-light scene shooting, ensuring night vision shooting and eliminating frequent camera switching.
- Built-in EIS and supports Gyroflow technology, taking you a smooth and stable video quality, to facilitate and enjoy freestyle fly.
- Comes with silicone pads for mounting the camera, ensuring stability and minimizing camera shake for perfect captures.
- Supports manual shutter and manual ISO settings, take perfect photos regardless of any lighting limits.

- The moonlight camera has a 160° FOV, providing you with a more natural and real picture for the ultimate flying experience.

- Come with ND8 filters to meet the needs of more different shooting scenes, to bring different effects to the shooting.

Specification

Model	Moonlight kit
Firmware name	AvatarMoonlight_Sky_X.X.X
Communication Frequency	5.725-5.850GHz
Transmitter Power (EIRP)	FCC:<30dBm; CE:<14dBm; SRRC:<20dBm; MIC:<25dBm
1/O Interface	JST1.0*4(Power in)JST0.8*6(USB)□Micro SD card Slot□IPEX-1
Sensor	Starlight sensor
FOV	Max 160°
Aperture	F2.1
Shutter	Rolling shutter
ISO	100-25600
Recording resolution	4K@30/60fps,2.7K@30/60fps,1080p@100/60fps,720p@60fps
Max Mbps	150Mbps
Video format	MP4 (H.264)
3D DNR	Support
Gyroflow	Support
Built-in EIS	Support
Wide Power Input	7.4V-25.2V
Power consumption	12V@1.4A, 8V@2.2A
Memory card type	U3 MicroSD, Max 256G
Camera size	19.6mm*19mm*24mm
VTX size	15.3mm*34.5mm*34.5mm
VTX Installation hole distance	20*20mm/25*25mm (M2)
Weight	38.5g(Antenna not included)
OSD	Canvas mode
Latency	Average delay 22ms
Antenna	2 (IPEX)
VTX Antenna	
model	avatar V2 antenna
Polarization	LHCP
Frequency range	5600MHz-6000MHz
Average Gain	1.9dBi
VSWR	□1.5
Input Impedance	50Ω
Interface	IPEX-1
Dimension	R15 X 45mm □without cable□
Weight	2g

Packing List□